

ATF 8 HP

Description

ATF 8 HP Fluid is an Automatic Transmission Fluid based on HC and PAO.

Benefits

- Highest Quality Features
- High load capacity and extremely wear-reducing
- Superior friction constant
- No foaming
- Minimal evaporation losses
- Excellent low-temperature switching behavior
- Adapted friction characteristics, for sporty gear changes
- Excellent oxidation and thermal stability
- No effect on usual sealing materials



Specification/Recommendations

- ◆ BMW L12108 (83 22 2 152 426)
- ◆ BMW 83 22 2 305 397
- ◆ BMW 83 22 2 289 720
- ◆ Chrysler 68157995AA
- ◆ Mopar 68157995AA
- ◆ Jaguar 02JDE 26444
- ◆ Land Rover LR 023288
- ◆ VW / Audi G 060 162 A1/A2/A6, G 055 162 (A2, A6)
- ◆ ZF Lifeguardfluid 8 (S671 090 312)

Typical Values	Method	Unit	ATF 8 HP
Density at 15°C	DIN 51 757	kg/m ³	844
Color	Visual		Green
Viscosity at 40°C	DIN 51 562	mm ² /s	26.9
Viscosity at 100°C	DIN 51 562	mm ² /s	5.6
Viscosity Index	DIN ISO 2909		157
Pour point	DIN ISO 3016	°C	-45
Flash point	DIN ISO 2592	°C	224

Our information is based on thorough research and maybe consider reliable, although not legally binding. The operating instruction and oil recommendation of vehicle and engine manufacturers must be followed.

VOLUME	1 ltr	4 tr	5 ltr	20 ltr	60 ltr	208 ltr

PACKAGING	1 Box 12 Pcs	1 Box 4 Pcs	1 Box 3 Pcs	1 Pc Can	1 Pc Drum	1 Pc Drum