

ATF DEXRON III H

Description

Procare ATF DX III H - fluid is an Automatic Transmission Fluid, which is made from mineral base oils and products from the synthetic technology, in combination with a special additive package.

Application

ATF Dexron III H is used in automatic vehicle gears, servo steering, fluid couplings and hydrodynamic converters as well as in hydraulics of passenger cars, commercial vehicles, busses and construction vehicles, if an ATF of Dexron III H - type is recommended.



Specification/Recommendations

- ◆ DEXRON III H und Dexron III G
- ◆ Ford M2C138-CJ, M2C 166-H
- ◆ MB 236.1, 236.5, 236.6 & 236.7
- ◆ MAN 339 Typ Z1 & V1, Z2 & V2
- ◆ ZF TE-ML 02F, 04D, 09,11A, 14A & 17C
- ◆ Ford Mercon
- ◆ Allison C-4
- ◆ Allison TES, 389
- ◆ Volvo 97340, 97341
- ◆ Voith 55.6335 & 55.6336

Typical Values	Method	Unit	ATF Dexron III H
Density at 15°C	DIN 51 757	kg/m ³	847
Viscosity at 40°C	DIN 51 562	mm ² /s	38
Viscosity at 100°C	DIN 51 562	mm ² /s	7.8
Viscosity Index	DIN ISO 2909		182
Pour point	DIN ISO 3016	°C	-50
Flash point	DIN ISO 2592	°C	228

Our information is based on thorough research and maybe consider reliable, although not legally binding. The operating instruction and oil recommendation of vehicle and engine manufacturers must be followed.

VOLUME	1 ltr	4 tr	5 ltr	20 ltr	60 ltr	208 ltr
PACKAGING	1 Box 12 Pcs	1 Box 4 Pcs	1 Box 3 Pcs	1 Pc Can	1 Pc Drum	1 Pc Drum