

ATF MB14

Description

ATF MB14 is a high performance ATF for life-time use in motorcar transmissions, especially of MB. It is made from synthetic base oils and such from the synthesis technology. The outstanding performance package, an extremely shear-stable VI-improver, modern anti-wear additives and balanced friction modifiers assure enduring excellent gear changing properties at modern automatic transmissions with controlled torque converter clutches.

ATF MB14 exceeds any Dexron III - requirements.

It is fully compatible and also miscible with Dexron IID- and Dexron III- ATFs .

Application

ATF MB14 is foreseen for automatic transmissions of motorcars, if an ATF according Dexron III, MB 236.12 or MB 236.14 is recommended.



Specification/Recommendations

- ◆ MB 236.12
- ◆ MB 236.14
- ◆ Audi G 052 162 (A1, A2)
- ◆ Porsche P/N 999 917 547 00
- ◆ PSA Peugeot/Citroen P/N Z 000169756
- ◆ Jaguar JLM 20238

Typical Values	Method	Unit	ATF MB14
Density at 15°C	DIN 51 757	kg/m ³	850
Color	Visual		red
Viscosity at 40°C	DIN 51 562	mm ² /s	37.3
Viscosity at 100°C	DIN 51 562	mm ² /s	7.0
Viscosity Index	DIN ISO 2909		151
Pour point	DIN ISO 3016	°C	-45
Flash point	DIN ISO 2592	°C	228

Our information is based on thorough research and maybe consider reliable, although not legally binding. The operating instruction and oil recommendation of vehicle and engine manufacturers must be followed.

VOLUME	1 ltr	4 tr	5 ltr	20 ltr	60 ltr	208 ltr
--------	-------	------	-------	--------	--------	---------

PACKAGING	1 Box 12 Pcs	1 Box 4 Pcs	1 Box 3 Pcs	1 Pc Can	1 Pc Drum	1 Pc Drum
-----------	-----------------	----------------	----------------	-------------	--------------	--------------