

ATF MB15

Description

ATF MB15 is a high performance ATF for use in the latest Mercedes-Benz 7-speed automatic transmission (NAG2FE+) from 21.06.2010.

It is based on fundamental oils from the synthesis technology and superior performance package.

An extremely shear stable VI improver in connection with modern anti-wear additives and friction modifiers guarantee stable lasting excellent smooth switching behavior, outstanding oxidation stability and a superior coefficient of friction stability. The lowered viscosity ensures maximum fuel economy.

Application

ATF MB15 is intended for use in the latest 7-speed automatic transmission from Mercedes-Benz. It is not backward compatible, so not suitable for use in older transmissions.

Note manufacturer's instructions!



Specification/Recommendations

◆ MB 236.15

Typical Values	Method	Unit	ATF MB15
Density at 15°C	DIN 51 757	kg/m ³	845
Appearance			blue
Viscosity at 40°C	DIN 51 562	mm ² /s	23.0
Viscosity at 100°C	DIN 51 562	mm ² /s	5.0
Viscosity Index	DIN ISO 2909		160
Flash point COC	DIN ISO 3016	°C	>190
Pour point	DIN ISO 2592	°C	-45

Our information is based on thorough research and maybe consider reliable, although not legally binding. The operating instruction and oil recommendation of vehicle and engine manufacturers must be followed.

VOLUME

1 ltr

4 tr

5 ltr

20 ltr

60 ltr

208 ltr

PACKAGING

1 Box
12 Pcs

1 Box
4 Pcs

1 Box
3 Pcs

1 Pc
Can

1 Pc
Drum

1 Pc
Drum