



ATF MVS

Description

ATF MVS fluid is an Automatic Transmission Fluid which is made by multi-vehicle anti-shudder additive technology optimized for passenger car applications.

ATF MVS is used in an extensive range of European and American passenger car service fill applications, it also can be used in commercial vehicle applications and power steering.

Benefits

- Exceptional oxidation behavior
- Anti-shudder durability
- Smoother shifts over a long period of time
- Excellent anti-rust properties
- Low foaming tendency

Specification/Recommendations

- ◆ GM DEXRON II / II-D / II-E / III-G / III-H
- ◆ Allison C-4, TES-295, TES-389
- ◆ BMW/Mini P/N 81 22 9 400 272/275
- ◆ BMW/Mini P/N 81 22 9 407 858/859
- ◆ BMW/Mini P/N 83 22 0 024 249/359
- ◆ BMW/Mini P/N 83 22 0 026 922 (BMW 7045 E)
- ◆ BMW/Mini P/N 83 22 0 402 413
- ◆ BMW/Mini P/N 83 22 0 403 248/249
- ◆ BMW/Mini P/N 83 22 7 542 290
- ◆ BMW/Mini P/N 83 22 9 407 765 (BMW LA 2634)
- ◆ Chrysler/Dodge/Jeep ATF+2/ATF+3/ATF+4
- ◆ Chrysler/Dodge/Jeep AS68RC ATF
- ◆ VW/Audi US 000 162
- ◆ Renault Matic D2
- ◆ Porsche P/N 999 917 547 00 (A2)
- ◆ Porsche P/N 000 043 204 41
- ◆ Mobil ATF 3309
- ◆ Shell 3403-M115, LA 2634
- ◆ Chrysler/Dodge/Jeep SP-III
- ◆ Daimler/Mercedes MB 236.5, 236.6, 236.7
- ◆ MB 236.8, 236.9, 236.10, 236.91
- ◆ FORD WSS-M2C919-E (Mercon V)
- ◆ FORD/Lincoln/Mercury P/N XT-2-QDX [M]
- ◆ FORD/Lincoln/Mercury P/N XT-2-QSM [Syn]
- ◆ FORD/Lincoln/Mercury P/N XT-5-QM or -DM [V]
- ◆ VW/Audi G 052 990 (A2), G 055 025 (A2)
- ◆ FORD/Lincoln/Mercury P/N XT-9-QMM5 [FNR5]
- ◆ FORD/Lincoln/Mercury WSS-M2C922-A1
- ◆ GM/GMC/Opel/Saturn P/N 19 40 700/767
- ◆ VW/Audi G 052 025 A2, G 052 055
- ◆ ZF TE-ML 11A / 11B
- ◆ Mercon V
- ◆ Renk Genuine Oil
- ◆ PSA Peugeot Citroen P/N Z 000169756
- ◆ VW/Audi G 052 162 (A1, A2)
- ◆ Voith H55.6335.XX
- ◆ MAN 339 A
- ◆ Volvo P/N 1161540 / 1161640
- ◆ GM/GMC/Opel/Saturn P/N 21005966 (transaxle)
- ◆ GM/GMC/Opel/Saturn P/N 22717466
- ◆ GM/GMC/Opel/Saturn P/N 88900925/9986195
- ◆ GM/GMC/Opel/Saturn T-IV, Type A Suffix A
- ◆ Jaguar JLM 20238 / 20292 / 21044 / K17
- ◆ FORD/Lincoln/Mercury P/N XT-8-QAW [Premium]
- ◆ Jaguar WSS-M2C922-A1
- ◆ Aisin Warner JWS 3309
- ◆ Land Rover Texaco ETL-7045E
- ◆ Voith Svc Bltn # 013 / 118
- ◆ Porsche P/N 000 043 205 09
- ◆ Volvo P/N 1161521
- ◆ Volvo P/N 1273,41
- ◆ Saab 3309 - T-IV
- ◆ Texaco ETL 7045E / 8072B, N402



Typical Values	Method	Unit	ATF MVS
Density at 15°C	DIN 51 757	kg/m ³	848
Color	Visual		red
Viscosity at 40°C	DIN 51 562	mm ² /s	38.2
Viscosity at 100°C	DIN 51 562	mm ² /s	7.0
Viscosity Index	DIN ISO 2909		150
Pour point	DIN ISO 3016	°C	-45
Flash point	DIN ISO 2592	°C	228

Our information is based on thorough research and maybe consider reliable, although not legally binding. The operating instruction and oil recommendation of vehicle and engine manufacturers must be followed.

VOLUME	1 ltr	4 tr	5 ltr	20 ltr	60 ltr	208 ltr

PACKAGING	1 Box 12 Pcs	1 Box 4 Pcs	1 Box 3 Pcs	1 Pc Can	1 Pc Drum	1 Pc Drum