

ATF SUFFIX A

Description

ATF Suffix A is an Automatic Transmission Fluid for the use in automatic gears and torque converters, if a gear oil is recommended, which meets the specifications described below. It is also used in manual transmissions, load change gears, power steering and hydraulics of motor cars.

ATF Suffix A is produced from highly refined base stocks. Approved additives provide a performance level, which features a very low pour point, a very high viscosity index and a good shear stability. It prevents deposits and protects the gear against corrosion. Its foaming tendency is very low, it provides best oxidation stability and a good compatibility with elastomeres.



Specification/Recommendations

- ◆ GM ATF Type A, Suffix A
- ◆ MB 236.2
- ◆ Renk (Doromat)
- ◆ MAN 339 TYPE A

Typical Values	Method	Unit	ATF Suffix A
Density at 15°C	DIN 51 757	kg/m ³	854
Viscosity at 40°C	DIN 51 562	mm ² /s	37.8
Viscosity at 100°C	DIN 51 562	mm ² /s	8.2
Viscosity Index	DIN ISO 2909		200
Pour point	DIN ISO 3016	°C	-45
Flash point	DIN ISO 2592	°C	219

Our information is based on thorough research and maybe consider reliable, although not legally binding. The operating instruction and oil recommendation of vehicle and engine manufacturers must be followed.

VOLUME	1ltr	4 tr	5ltr	20ltr	60ltr	208ltr
PACKAGING	1 Box 12 Pcs	1 Box 4 Pcs	1 Box 3 Pcs	1 Pc Can	1 Pc Drum	1 Pc Drum