

GEAR OIL 80W-90 GL-4

Description

Gear Oil 80W-90 GL-4 gear oils are designed to be used in synchronised and non-synchronised manual transmissions. Furthermore they are applicable for the lubrication of certain steering transmissions and transaxles.

Benefits

Gear Oil 80W-90 GL-4 gear oils assure poor in wear transmission of high torques, even at changing speeds. Also at extreme flank pressures metal contact or even scuffing are effectively prevented.

- Good cold flow properties
- High aging stability
- Low foaming tendency
- High shear stability
- Assured corrosion protection
- Elastomer compatibility



Specification/Recommendations

- ◆ API GL-4
- ◆ MB 235.1

- ◆ ZF TE-ML 06L, 08, 16A, 17A, 19A, 19C
- ◆ MAN 341 E-1

Typical Values	Method	Unit	Gear Oil 80W-90 GL-4
Density at 15°C	DIN 51 757	kg/m ³	898
Viscosity at 40°C	DIN 51 562	mm ² /s	166
Viscosity at 100°C	DIN 51 562	mm ² /s	16.3
Pour point	DIN ISO 3016	°C	-33
Flash point	DIN ISO 2592	°C	222
FZG-test A/16,6/90 Damage loading step	DIN 51 534		>12

Our information is based on thorough research and maybe consider reliable, although not legally binding. The operating instruction and oil recommendation of vehicle and engine manufacturers must be followed.

VOLUME	1 ltr	4 tr	5 ltr	20 ltr	60 ltr	208 ltr

PACKAGING	1 Box 12 Pcs	1 Box 4 Pcs	1 Box 3 Pcs	1 Pc Can	1 Pc Drum	1 Pc Drum