

## PRODUCT INFORMATION

# SYNGEAR 75W-80

## Description

**Syngear 75W-80** is made from high quality HC-synthetic base oils. In combination with a modern additive-package there is achieved a performance level.

**Syngear 75W-80** is used for the lubrication of synchronized and non-synchronized standard transmissions. Especially it is recommended for commercial vehicles, which are furnished with BMW, VW and Mercedes Benz manual transmissions.

## Benefits

- Excellent high pressure and wear protection properties.
- Very good properties in corrosion and rust protection.
- Low foaming tendency and excellent aging stability.
- Reduced oil consumption and extended oil drain intervals.
- High viscosity index and low pour point care for easy gear changing even at hot temperatures.



## Specification/Recommendations

- ◆ API GL-4
- ◆ BMW MTF LT-1/-2/-3/-4
- ◆ FORD WSS-M2C200-C / D2
- ◆ GM 194004/19259104 (BOT 303)
- ◆ GM 1940182 / 1940764 / 1940768
- ◆ MB 235.10
- ◆ NISSAN MT-XZ / MT-XZ TL (JR Type)
- ◆ PSA B 71 2330
- ◆ Special Gear Oil, MTF 94
- ◆ Special Honda MTF/MTF-II/MTF-III
- ◆ Tranself NFJ, NFP, TRJ, TRT, TRZ
- ◆ Volvo 97308 / 97309
- ◆ VW G009 317, VW G052 171, G052 178
- ◆ VW G052 512, G052 726, VW G060 726
- ◆ VW G 50, G052 527 A2, G070 726 A2

Typical Values	Method	Unit	Syngear 75W-80
Density at 15°C	DIN 51 757	kg/m <sup>3</sup>	855
Viscosity at 40°C	DIN 51 562	mm <sup>2</sup> /s	51.2
Viscosity at 100°C	DIN 51 562	mm <sup>2</sup> /s	9.1
Viscosity index	DIN ISO 2909		161
Pour point	DIN ISO 3016	°C	-42
Flash point	DIN ISO 2592	°C	215

Our information is based on thorough research and maybe consider reliable, although not legally binding. The operating instruction and oil recommendation of vehicle and engine manufacturers must be followed.

VOLUME	1 ltr	4 tr	5 ltr	20 ltr	60 ltr	208 ltr

PACKAGING	1 Box 12 Pcs	1 Box 4 Pcs	1 Box 3 Pcs	1 Pc Can	1 Pc Drum	1 Pc Drum