

PRODUCT INFORMATION

BRAKE FLUID DOT 4 LV

Description

Brake Fluid DOT 4 LV is a synthetic 'low viscosity' high-performance brake fluid with a boiling point of at least 265°C and a wet boiling point of at least 170°C, and therefore ideal for hydraulic brake and clutch systems.

Brake Fluid DOT 4 LV is suitable for motor car brake systems DOT 3 / DOT 4. The product is completely compatible with comparably brake fluids. In order to achieve full performance it is recommended to use only **Brake Fluid DOT 4 LV** for re-filling.



Properties

- Wet boiling point > 170°C
- Boiling point > 265°C

Benefits

- High operating reliability, even after prolonged use.
- Better brake response at temperatures of up to 40°C.
- Miscible with brake fluids of equal specification.

Specification/Recommendations

- ◆ DOT 4, exceeds DOT 3
- ◆ FMVSS 116
- ◆ SAE J 1704
- ◆ ISO 4925 Class 6

Special Hints

Brake Fluid DOT 4 LV to be stored only originally sealed. Straight after use the brake fluid container has to be sealed airtight again. Necessarily follow the service instructions for re-filling.

For re-filling hydraulic brake systems absolute cleanliness is required.

The fluid may be harmful for vehicle paintwork.

Brake fluids have to be separately collected and disposed. They must not be mixed-up with waste oil.

Our information is based on thorough research and maybe consider reliable, although not legally binding. The operating instruction and oil recommendation of vehicle and engine manufacturers must be followed.

VOLUME	1 ltr	4 tr	5 ltr	20 ltr	60 ltr	208 ltr
PACKAGING	1 Box 12 Pcs	1 Box 4 Pcs	1 Box 3 Pcs	1 Pc Can	1 Pc Drum	1 Pc Drum