

PRODUCT INFORMATION

PRO CARE COOLANT C12 PLUS

Description

Procare Coolant C12 Plus is a coolant based on ethylenglycole, to be used for all motor vehicles, which require silicate-free products (e.g. Ford, GM and MAN). It is applicable for all established engines inclusive the modern high performance aluminium-motors. It is compatible with all coolant brands(also C11).

Application

- ✓ May be used a life time through for grey iron - and all motors.
- ✓ Protects all metallic materials in the system.
- ✓ Is eco friendly, because it is free of nitrites, amines, phosphates and silicates.
- ✓ Provides all-seasons protection of the cooling system.

Specification/Approval

- ◆ VW/Audi/Seat/Skoda TL744-D/F (G12/12+)
- ◆ MB 325.3
- ◆ John Deere JDM H5
- ◆ MAN 324 SNF
- ◆ Opel-GM GMW 3420
- ◆ MTU MTL 504B
- ◆ Renault-Nissan 41-01-001/-S Type D
- ◆ Fiat MAT3624
- ◆ Caterpillar A4.05.09.01
- ◆ Jenbacher TA 1000-0201
- ◆ Mazda MEZ MN 121 D
- ◆ Liebherr MD1-36-130
- ◆ Cummins IS series u N14
- ◆ Ford WSS-M97B44-D
- ◆ Komatsu 07.892 (2009)
- ◆ Deutz/MWM 0199-99-2091/8
- ◆ Volvo 014 GS 17009



Typical Values	Unit	ProCare Coolant C12 Plus
Density at 20°C	kg/m ³	1076
Colour	-	violet
Pour Point	°C	-40
Flash Point	°C	>100
pH (35%)	-	8.6
Boiling Point	°C	>100

VOLUME	1.5 ltr	5 ltr	20 ltr	60 ltr	208 ltr
--------	---------	-------	--------	--------	---------

PACKAGING	1 Box 12 Pcs	1 Box 3 Pcs	1 Pc Can	1 Pc Drum	1 Pc Drum
-----------	-----------------	----------------	-------------	--------------	--------------