

## PRODUCT INFORMATION

# PRO CARE COOLANT C13

## Description

Procure Coolant C13 is a ready water-diluted modern antifreeze based on ethylenglycole, to be used for motor vehicles with engines of cast iron, aluminum and / or from the combination of both metals. Procure Coolant C13 is particularly recommended for light metal engines where a special aluminum protection is required at higher temperatures.

## Application

- ✓ Provides long lasting protection due to the combination of the organic inhibitors.
- ✓ Forms a homogeneous protective layer due to the sophisticated additive package.
- ✓ Offers thanks to highly effective additives to protect all metals, including aluminum.
- ✓ Is environmentally friendly, being free of nitrite, amine, phosphate and borate.



## Specification/Approval

- ◆ Audi / Seat / Skoda / VW - TL774J (G13)

Typical Values	Unit	ProCare Coolant C13
Density at 20°C	kg/m <sup>3</sup>	1140
Colour	-	Red / Violet
Flash Point	°C	>100
pH	-	8.4
Boiling Point	°C	>170

VOLUME	1.5 ltr	5 ltr	20 ltr	60 ltr	208 ltr
--------	---------	-------	--------	--------	---------

PACKAGING	1 Box 12 Pcs	1 Box 3 Pcs	1 Pc Can	1 Pc Drum	1 Pc Drum
-----------	-----------------	----------------	-------------	--------------	--------------