

PRO CARE COOLANT C11

Description

Procare Coolant C 11-Concentrate is a coolant based on ethylenglycole. It is free of amines, nitrites and phosphates. The special inhibitor-package protects outstandingly the engine and the cooling circuit against frost, rust and excessive heat. It is also applicable for light metal motors.

Application

Procare Coolant C 11-Concentrate is a coolant, which only may be used water-mixed.

It is miscible with tap water. In order to assure sufficient corrosion protection a minimum amount of coolant concentrate in tap water should not fall below a value of 35%, which especially should be regarded for the use in summer.

It is recommended to renew the coolant at least after 5 years usage. If the motor manufacturer has specified the use of silicate-free product the according user manual has to be regarded (VW, Audi, Seat, Skoda, Ford, GM/Opel from 1997).

Specification/Approval

- ◆ MB 325.0 & 325.2
- ◆ BMW GS 94000
- ◆ MAN 324 NF
- ◆ JASO M325 (Japan)
- ◆ KSM 2142
- ◆ BT-PS-606 A (MIL Belgium)
- ◆ VW / Audi / Seat / Skoda / Porsche TL 774-C (G11)
- ◆ Opel GME L301
- ◆ Saab 6901 599
- ◆ BS 6580
- ◆ SAE J1034
- ◆ Swiss Fed. Lab Empa
- ◆ FS 6850-0951 (MIL Norway)
- ◆ Ford ESD-M97B94-A
- ◆ MTU MTL 5048
- ◆ Cummins 85T8
- ◆ Volvo 128 6083/002
- ◆ NATO S-759
- ◆ FSD 8704 (MIL Sweden)
- ◆ DCSEA 615/C (MIL France)
- ◆ ASTM D3306
- ◆ ASTM D4656
- ◆ NFR 15-601
- ◆ FVW Heft R443 (Germany)
- ◆ E/L-1415b (MIL Italy)
- ◆ TL 6850-0038 (MIL Germany)
- ◆ Lada TTM VAZ 1.97.717-97uASTM D4958



Typical Values	Unit	ProCare Coolant C11
Density at 20°C	kg/m ³	1129
Colour	-	Blue
Flash Point	°C	>120
pH (35%)	-	8.2
Boiling Point	°C	>150

VOLUME	1.5 ltr	5 ltr	20 ltr	60 ltr	208 ltr
--------	---------	-------	--------	--------	---------

PACKAGING	1 Box 12 Pcs	1 Box 3 Pcs	1 Pc Can	1 Pc Drum	1 Pc Drum
-----------	-----------------	----------------	-------------	--------------	--------------