

PRODUCT INFORMATION

PRO CARE COOLANT C11

Description

Procare Coolant C 11-Concentrate is a coolant based on ethylenglycole. It is free of amines, nitrites and phosphates. The special inhibitor-package protects outstandingly the engine and the cooling circuit against frost, rust and excessive heat. It is also applicable for light metal motors.

Application

Procare Coolant C 11-Concentrate is a coolant, which only may be used water-mixed.

It is miscible with tap water. In order to assure sufficient corrosion protection a minimum amount of coolant concentrate in tap water should not fall below a value of 35%, which especially should be regarded for the use in summer.

It is recommended to renew the coolant at least after 5 years usage. If the motor manufacturer has specified the use of silicate-free product the according user manual has to be regarded (VW, Audi, Seat, Skoda, Ford, GM/Opel from 1997).

Specification/Approval

- | | | | |
|--|----------------------------|--------------------------------------|-----------------------------|
| ◆MB 325.0 & 325.2 | ◆Opel GME L301 | ◆Ford ESD-M97B94-A | ◆ASTM D3306 |
| ◆BMW GS 94000 | ◆Saab 6901 599 | ◆MTU MTL 5048 | ◆ASTM D4656 |
| ◆MAN 324 NF | ◆BS 6580 | ◆Cummins 85T8 | ◆NFR 15-601 |
| ◆JASO M325 (Japan) | ◆SAE J1034 | ◆Volvo 128 6083/002 | ◆FVV Heft R443 (Germany) |
| ◆KSM 2142 | ◆Swiss Fed. Lab Empa | ◆NATO S-759 | ◆E/L-1415b (MIL Italy) |
| ◆BT-PS-606 A (MIL Belgium) | ◆FS 6850-0951 (MIL Norway) | ◆FSD 8704 (MIL Sweden) | ◆TL 6850-0038 (MIL Germany) |
| ◆VW / Audi / Seat / Skoda / Porsche TL 774-C (G11) | ◆DCSEA 615/C (MIL France) | ◆Lada TTM VAZ 1.97.717-97uASTM D4958 | |



Typical Values	Unit	ProCare Coolant C11
Density at 20°C	kg/m ³	1129
Colour	-	Green
Flash Point	°C	>120
pH (35%)	-	8.2
Boiling Point	°C	>150

VOLUME

1.5 ltr 5 ltr 20 ltr 60 ltr 208 ltr

PACKAGING

1 Box
12 Pcs 1 Box
3 Pcs 1 Pc
Can 1 Pc
Drum 1 Pc
Drum