

PRODUCT INFORMATION

PRO CARE COOLANT C12

Description

Procare Coolant C12 is a coolant based on ethylenglycole, to be used for all motor vehicles, which require silicate-free products (e.g. Ford, GM and MAN). It is applicable for all established engines inclusive the modern high performance aluminium-motors. It is compatible with all coolant brands (also C11).

Application

- ✓ May be used a life time through for grey iron - and all motors.
- ✓ Protects all metallic materials in the system.
- ✓ Is eco friendly, because it is free of nitrites, amines, phosphates and silicates.
- ✓ Provides all-seasons protection of the cooling system.

Specification/Approval

- | | | | |
|------------------------------------------|----------------------------|------------------|-----------------------------|
| ◆ VW/Audi/Seat/Skoda TL774-D/F (G12/12+) | ◆ ADE | ◆ ASTM D3306 | ◆ MB 325.3 |
| ◆ Bergen Engines 2.13.01 | ◆ DAF 74002 | ◆ Aston Martin | ◆ NFR 15-601 |
| ◆ Case New Holland MAT3624 | ◆ Detroit DFS93K217 | ◆ Behr | ◆ E/L-1415b (MIL-Italy) |
| ◆ Caterpillar A4.05.09.01 | ◆ Deutz DQC CB-14 | ◆ Chevrolet | ◆ ASTM D4656 |
| ◆ Cummins CES 14603/CES 14439 | ◆ Fiat MAT3624 | ◆ Claas | ◆ ASTM D4985 |
| ◆ Cummins IS series u N14 | ◆ Ford WSS-M97B44-D | ◆ Fendt | ◆ JASO M325 |
| ◆ Deutz/MWM 0199-99-2091/8 | ◆ Foton Q-FPT 2313005-2013 | ◆ Great Wall | ◆ NATO S-759 |
| ◆ Jaguar STJLR 651.5003 | ◆ Jaguar CMR 8229 | ◆ Hitachi | ◆ ASTM D6210 |
| ◆ John Deere JDM H5 | ◆ Jenbacher TA 1000-0201 | ◆ Isuzu | ◆ KSM 2142 |
| ◆ Komatsu 07.892 (2009) | ◆ Liebherr MD1-36-130 | ◆ Karosa | ◆ Onorm V5123 |
| ◆ Land-Rover STJLR 651.5003 | ◆ MAK A4.05.09.01 | ◆ Kobelco | ◆ BT-PS-606 A (MIL-Belgium) |
| ◆ Leyland Trucks DW03245403 | ◆ MAN 324 SNF | ◆ Proton | ◆ FSD 8704 (MIL-Sweden) |
| ◆ Mack 014 GS 17009 | ◆ MAN B&W AG D36 5600 | ◆ Rover | ◆ FVV Heft R443 (Germany) |
| ◆ Opel-GM GMW 3420 | ◆ Mazda MEZ MN 121 D | ◆ Santana Motors | ◆ BR 637 |
| ◆ Renault Trucks 41-01-001/-S Type D | ◆ Mitsubishi MHI | ◆ Saturn | ◆ SAE J1034 |
| ◆ SACM Diesel DLP799861 | ◆ MTU MTL 5048 | ◆ Semt Pielstick | ◆ BS 6580 |
| ◆ Vauxhall GM 6277M (+B040 1065) | ◆ Saab B 040 1065 | ◆ Tedom | ◆ DCSEA 615/C (MIL-France) |
| ◆ Vauxhall GME L1301 | ◆ Skoda 61-0-0257 | ◆ Thermo King | ◆ UNE 26-361-88/1 |
| ◆ Volvo 014 GS 17009 | ◆ Wartsilä 32-9011 | ◆ Valtra | |
| ◆ Volvo Penta/Trucks/Construction | ◆ Waukesha | ◆ Yanmar | |



Typical Values	Unit	ProCare Coolant C12
Density at 20°C	kg/m ³	1112
Colour	-	violet
Flash Point	°C	>100
pH (35%)	-	8.3
Boiling Point	°C	>170

VOLUME	1.5 ltr	5 ltr	20 ltr	60 ltr	208 ltr
--------	---------	-------	--------	--------	---------

PACKAGING	1 Box 12 Pcs	1 Box 3 Pcs	1 Pc Can	1 Pc Drum	1 Pc Drum
-----------	-----------------	----------------	-------------	--------------	--------------