

PROGUARD SYNTECH 4T 10W-40

Description

Proguard Syntech 4T 10W-40 is a high performance special engine oil for motor cycles with air- and water-cooled 4-stroke engines of highest output. It is the ideal partner for all sportive motor-cycles, on all roads and off-road. The high capacity is assured by a combination of high quality base oils with successfully tested additives.

Benefits

- Optimal lubrication in motor and in gear and assured functionality of wet clutches even at extreme operating conditions and continuous use.
- Outstanding motor cleanliness, especially at pistons and valves.
- Good cold-starting properties.



Specification/Recommendations

- ◆ API SN
- ◆ ACEA A3
- ◆ JASO MA2

Typical Values	Method	Unit	4T 10W-40
Density at 15°C	DIN 51 757	kg/m ³	863
Viscosity at 40°C	DIN 51 562	mm ² /s	97.5
Viscosity at 100°C	DIN 51 562	mm ² /s	15.1
Viscosity Index	DIN ISO 2909		161
Dynamic Viscosity at -25°C	DIN 51 377	mPa.s	5590
Pour point	DIN ISO 3016	°C	-39
Flash point	DIN ISO 2592	°C	232
TBN	DIN ISO 3771	mg KOH/g	10.5

Our information is based on thorough research and maybe consider reliable, although not legally binding. The operating instruction and oil recommendation of vehicle and engine manufacturers must be followed.

VOLUME	1 ltr	4 tr	5 ltr	20 ltr	60 ltr	208 ltr
PACKAGING	1 Box 12 Pcs	1 Box 4 Pcs	1 Box 3 Pcs	1 Pc Can	1 Pc Drum	1 Pc Drum