

PRODUCT INFORMATION

MULTI 20W-20

Description

Multi 20W-20 monograde engine oils are developed for gasoline- and diesel engines, which because of their type of application do not require higher-alloyed engine oils.

Benefits

- prevent built-up of aging products at high temperatures.
- provide good cleaning capability and dirt holding capacity.
- protect the engine against corrosion and wear.
- hold capacity reserves even at high motor loadings.

Application

Multi 20W-20 monograde engine oils are cost-effective HD-oils for gasoline and diesel engines. They are also used for heavy-duty diesel engines in commercial vehicles (with and without charging).

According constructor recommendations they can be used as compressor oils according DIN 51 506 VC-L .

Specification/Recommendations

◆ API SF / CD

◆ DIN 51 506 (Air compressor oil VC-L)

Typical Values	Method	Unit	Multi 20W-20
Density at 15°C	DIN 51 757	kg/m ³	860
Viscosity at 40°C	DIN 51 562	mm ² /s	50
Viscosity at 100°C	DIN 51 562	mPa.s	7.5
Dynamic Viscosity at ()°C	DIN 51 377	mPa.s	6300(-15)
Pourpoint	DIN ISO 3016	°C	-33
Flash point	DIN ISO 2592	°C	236
TBN	DIN ISO 3771	mg KOH/g	5.5

Our information is based on thorough research and maybe consider reliable, although not legally binding. The operating instruction and oil recommendation of vehicle and engine manufacturers must be followed.



VOLUME

1 ltr

4 tr

5 ltr

20 ltr

60 ltr

208 ltr

PACKAGING

1 Box
12 Pcs

1 Box
4 Pcs

1 Box
3 Pcs

1 Pc
Can

1 Pc
Drum

1 Pc
Drum