

PREMIUM SYNTHETIC SAE 20W-50

Description

Premium Synthetic SAE 20W-50 is a high performance low friction oil to be used in gasoline passenger cars . It is produced by blending high quality synthetic oils and mineral base stocks and additives of most progressive technology.

Suitable also under severe operating conditions in modern passenger car engines, turbo or non-turbo charged, and for vans , too.

Premium Synthetic SAE 20W-50 by its optimized formulation provides lowered fuel and oil consumption. Because of its extended viscosity range the all seasons use is possible. A special booster raises the quality level up to API SN, which provides improved oxidation resistance, improved deposit protection, better wear protection, and better low-temperature performance over the life of the oil. This leads to an improved motor cleanliness and at least to an extended motor life.



Specification/Recommendations

- ◆ ACEA A3 /B4
- ◆ API SN / CF

Typical Values	Method	Unit	Premium Synthetic SAE 20W-50
Density at 15°C	DIN 51 757	kg/m ³	867
Viscosity at 40°C	DIN 51 562	mm ² /s	113
Viscosity at 100°C	DIN 51 562	mm ² /s	16.7
Viscosity index	DIN ISO 2909		161
CCS at -25°C	DIN 51 377	mPa.s	2136
Pour point	DIN ISO 3016	°C	-45
Flash point	DIN ISO 2592	°C	220
TBN	DIN ISO 3771	mg KOH/g	13.1

Our information is based on thorough research and maybe consider reliable, although not legally binding. The operating instruction and oil recommendation of vehicle and engine manufacturers must be followed.

VOLUME	1 ltr	4 tr	5 ltr	20 ltr	60 ltr	208 ltr

PACKAGING	1 Box 12 Pcs	1 Box 4 Pcs	1 Box 3 Pcs	1 Pc Can	1 Pc Drum	1 Pc Drum