

SPECIAL SYNTHETIC GM 5W-30

Description

Special Synthetic GM 5W-30 is a modern multigrade low friction engine oil of the latest generation for all-seasons use. The combination of unconventional hydrocrack base oils with the most modern additive technology assures a low viscous, shear-stable motor oil, which safely prevents deposits, lowers frictional losses of the motor and optimally protects against wear. This leads to fuel economy and concurrently to extended motor life.

Application

Special Synthetic GM 5W-30 is especially recommended for OPEL - gasoline and diesel engines, turbo charger and catalytic converter included. Constructor regulations to be regarded.



Specification/Recommendations

- ◆ ACEA C3
- ◆ GM dexos 2
- ◆ Opel GM-LL-B-025
- ◆ API SN / CF
- ◆ Opel GM-LL-A-025

Typical Values	Method	Unit	Special Synthetic GM 5W-30
Density at 15°C	DIN 51 757	kg/m ³	853
Density at 40°C	DIN 51 562	mm ² /s	65.8
Viscosity at 100°C	DIN 51 562	mm ² /s	11.4
Viscosity index	DIN ISO 2909		165
CCS at -30°C	DIN 51 377	mPa.s	5080
Pour point	DIN ISO 3016	°C	-42
Flash point	DIN ISO 2592	°C	226

Our information is based on thorough research and maybe consider reliable, although not legally binding. The operating instruction and oil recommendation of vehicle and engine manufacturers must be followed.

VOLUME	1 ltr	4 tr	5 ltr	20 ltr	60 ltr	208 ltr
PACKAGING	1 Box 12 Pcs	1 Box 4 Pcs	1 Box 3 Pcs	1 Pc Can	1 Pc Drum	1 Pc Drum