

PRODUCT INFORMATION

SUPER HIGH PERFORMANCE DIESEL 15W-40

Description

Super High Performance Diesel 15W-40 is a high performance motor oil for modern heavily stressed diesel engines inclusive turbo charger. Because of its outstanding additive technology it also comes up to the most severe requirements of gasoline engines. This makes it being excellent provider for mixed-fleet.

Benefits

- Excellent thermal/oxidative stability reduces sludge built-up and deposits.
- Allows maximum oil drain intervals by highest TBN-reserve.
- Minimizes efficiently bore polishing.
- Reduces oil aging, even at high temperatures.
- Best seal and elastomer compatibility.
- An all-seasons oil for mixed-fleet.

Super High Performance Diesel 15W-40 is especially recommended for fleets operating in severe on and off-highway service applications.



Specification/Recommendations

- ◆ ACEA E7
- ◆ API CI-4 / SL
- ◆ Global DHD-1
- ◆ MB 228.3
- ◆ Cummins CES 20077 / 20078
- ◆ MTU Type 2.0
- ◆ Caterpillar ECF-1a / ECF-2
- ◆ Renault RLD1 / RLD2
- ◆ MAN M 3275
- ◆ DDC 93K215
- ◆ JASO DH-1
- ◆ VOLVO VDS-3
- ◆ DEUTZ DQC III-10
- ◆ Mack EO-M Plus / EO-N

Typical Values	Method	Unit	Super High Performance Diesel 15W-40
Density at 15°C	DIN 51 757	kg/m ³	862
Viscosity at 40°C	DIN 51 562	mm ² /s	94.9
Viscosity at 100°C	DIN 51 562	mm ² /s	14.5
Viscosity Index	DIN ISO 2909		158
CCS at -20°C	DIN 51 377	mPa.s	3720
Pour point	DIN ISO 3016	°C	-42
Flash point	DIN ISO 2592	°C	232
TBN	DIN ISO 3771	mg KOH/g	11.3

Our information is based on thorough research and maybe consider reliable, although not legally binding. The operating instruction and oil recommendation of vehicle and engine manufacturers must be followed.

VOLUME	1 ltr	4 tr	5 ltr	20 ltr	60 ltr	208 ltr
PACKAGING	1 Box 12 Pcs	1 Box 4 Pcs	1 Box 3 Pcs	1 Pc Can	1 Pc Drum	1 Pc Drum