

PRODUCT INFORMATION

SUPER POWER DIESEL 15W-40

Description

Super Power Diesel 15W-40 is designed to be a high performance multigrade oil for diesel- and gasoline engines in light-duty commercial vehicles and passenger cars, the progressive features of which (lean-burn, turbo charger) are setting special requirements on the lubricant.

Because it is applicable both in PC-engines and in heavy-duty diesel engines of trucks, it represents the perfect lubricant to provide mixed-fleets.

Super Power Diesel 15W-40 is produced of high-quality base oils, which combined with modern additives and a shear-stable VI-improver are added up to a lubricant, which may be applied long-term and all seasons. Withal the engine permanently is protected against corrosion and wear.

Due to the balanced additive combination, oil-aging and sludge built-up are prevented efficiently.

Specification/Recommendations

- ◆ ACEA E2
- ◆ ACEA B3
- ◆ API CF-4 / CF / SJ
- ◆ MB 228.1
- ◆ MAN 271
- ◆ Volvo VDS



Typical Values	Method	Unit	SUPER POWER DIESEL 15W-40
Density at 15°C	DIN 51 757	kg/m ³	860
Viscosity at 40°C	DIN 51 562	mm ² /s	92.5
Viscosity at 100°C	DIN 51 562	mm ² /s	14.3
Viscosity Index	DIN ISO 2909		160
CCS at -20°C	DIN 51 377	mPa.s	5920
Pourpoint	DIN ISO 3016	°C	-39
Flash point	DIN ISO 2592	°C	230
TBN	DIN ISO 3771	mg KOH/g	8.6

Our information is based on thorough research and maybe consider reliable, although not legally binding. The operating instruction and oil recommendation of vehicle and engine manufacturers must be followed.

VOLUME

1 ltr

4 tr

5 ltr

20 ltr

60 ltr

208 ltr

PACKAGING

1 Box
12 Pcs

1 Box
4 Pcs

1 Box
3 Pcs

1 Pc
Can

1 Pc
Drum

1 Pc
Drum